

# ATC 100 B Series Porcelain Superchip® Multilayer Capacitors

- Case B Size (.110" x .110")
- Capacitance Range 0.1 pF to 1000 pF
- High Q
- Ultra-Stable Performance
- Low ESR/ESL
- High Self-Resonance
- Low Noise
- Established Reliability (QPL)
- Extended WVDC up to 1500 VDC

ATC, the industry leader, offers new improved ESR/ESL performance for the 100 B Series RF/Microwave Capacitors. This Series is now available with extended operating temperatures up to 175°C. High Density porcelain construction provides a rugged, hermetic package.

Typical functional applications: Bypass, Coupling, Tuning, Feedback, Impedance Matching and DC Blocking.

Typical circuit applications: UHF/Microwave RF Power Amplifiers, Mixers, Oscillators, Low Noise Amplifiers, Filter Networks, Timing Circuits and Delay Lines.

## ENVIRONMENTAL TESTS

ATC 100 B Series Capacitors are designed and manufactured to meet and exceed the requirements of EIA-198, MIL-PRF-55681 and MIL-PRF-123.

**THERMAL SHOCK:** MIL-STD-202, Method 107, Condition A.

**MOISTURE RESISTANCE:** MIL-STD-202, Method 106.

### LOW VOLTAGE HUMIDITY:

MIL-STD-202, Method 103, Condition A, with 1.5 Volts DC applied while subjected to an environment of 85°C with 85% relative humidity for 240 hours min.

### LIFE TEST:


MIL-STD-202, Method 108, for 2000 hours, at 125°C.

Voltage Applied:

200% of WVDC for capacitors rated at 500 volts DC or less.

120% of WVDC for capacitors rated at 1250 volts DC or less.

100% of WVDC for capacitors rated above 1250 volts DC.



## ELECTRICAL AND MECHANICAL SPECIFICATIONS

**QUALITY FACTOR (Q):** greater than 10,000 at 1 MHz.

### TEMPERATURE COEFFICIENT OF CAPACITANCE (TCC):

+90 ±20 PPM/°C (-55°C to +125°C)  
+90 ±30 PPM/°C (+125°C to +175°C)

### INSULATION RESISTANCE (IR):

0.1 pF to 470 pF:

10<sup>6</sup> Megohms min. @ +25°C at rated WVDC.

10<sup>5</sup> Megohms min. @ +125°C at rated WVDC.

510 pF to 1000 pF:

10<sup>5</sup> Megohms min. @ +25°C at rated WVDC.

10<sup>4</sup> Megohms min. @ +125°C at rated WVDC.

IR above +125°C is derated by one order of magnitude.

**WORKING VOLTAGE (WVDC):** See Capacitance Values Table, page 2.

### DIELECTRIC WITHSTANDING VOLTAGE (DWV):

250% of WVDC for capacitors rated at 500 volts DC or less for 5 seconds.

150% of WVDC for capacitors rated at 1250 volts DC or less for 5 seconds.

120% of WVDC for capacitors rated above 1250 volts DC for 5 seconds.

**RETRACE:** Less than ±(0.02% or 0.02 pF), whichever is greater.

**AGING EFFECTS:** None

### PIEZOELECTRIC EFFECTS:

None (No capacitance variation with voltage or pressure).

**CAPACITANCE DRIFT:** ±(0.02% or 0.02 pF), whichever is greater.

### OPERATING TEMPERATURE RANGE:

0.1 to 330 pF: from -55°C to +175°C

360 to 1000 pF: from -55°C to +125°C

### TERMINATION STYLES:

Available in various surface mount and leaded styles.

See Mechanical Configurations, page 3.

**TERMINAL STRENGTH:** Terminations for chips and pellets withstand a pull of 5 lbs. min., 15 lbs. typical, for 5 seconds in direction perpendicular to the termination surface of the capacitor. Test per MIL-STD-202, method 211.



AMERICAN

ATC North America  
sales@atceramics.com

TECHNICAL

ATC Europe  
sales@atceramics.com

CERAMICS

ATC Asia  
sales@atceramics-asia.com



THE  
ENGINEERS'  
CHOICE®

ISO 9001 REGISTERED  
COMPANY

THE ENGINEERS' CHOICE®

www.atceramics.com

ATC # 001-807 Rev. S; 8/18

# ATC 100 B Capacitance Values

| CAP. CODE | CAP. (pF) | TOL.    | RATED WVDC STD. | EXT. | CAP. CODE | CAP. (pF) | TOL.          | RATED WVDC STD. | EXT. | CAP. CODE | CAP. (pF) | TOL.          | RATED WVDC STD. | EXT. | CAP. CODE | CAP. (pF) | TOL. | RATED WVDC STD. | EXT. |
|-----------|-----------|---------|-----------------|------|-----------|-----------|---------------|-----------------|------|-----------|-----------|---------------|-----------------|------|-----------|-----------|------|-----------------|------|
| 0R1       | 0.1       | B       |                 |      | 2R4       | 2.4       |               |                 |      | 200       | 20        |               |                 |      | 151       | 150       |      |                 |      |
| 0R2       | 0.2       |         |                 |      | 2R7       | 2.7       |               |                 |      | 220       | 22        |               |                 |      | 161       | 160       |      |                 |      |
| 0R3       | 0.3       | B, C    |                 |      | 3R0       | 3.0       |               |                 |      | 240       | 24        |               |                 |      | 181       | 180       |      | 300             | 1000 |
| 0R4       | 0.4       |         |                 |      | 3R3       | 3.3       |               |                 |      | 270       | 27        |               |                 |      | 201       | 200       |      |                 |      |
| 0R5       | 0.5       |         |                 |      | 3R6       | 3.6       |               |                 |      | 300       | 30        |               |                 |      | 221       | 220       |      |                 |      |
| 0R6       | 0.6       |         |                 |      | 3R9       | 3.9       | B, C, D       |                 |      | 330       | 33        |               |                 |      | 241       | 240       |      |                 |      |
| 0R7       | 0.7       |         |                 |      | 4R3       | 4.3       |               |                 |      | 360       | 36        |               |                 |      | 271       | 270       |      |                 |      |
| 0R8       | 0.8       |         |                 |      | 4R7       | 4.7       |               |                 |      | 390       | 39        |               |                 |      | 301       | 300       |      |                 |      |
| 0R9       | 0.9       |         |                 |      | 5R1       | 5.1       |               |                 |      | 430       | 43        |               |                 |      | 331       | 330       |      | 200             | 600  |
| 1R0       | 1.0       |         |                 |      | 5R6       | 5.6       |               |                 |      | 470       | 47        |               | 500             | 1500 | 361       | 360       |      |                 |      |
| 1R1       | 1.1       | B, C, D | 500             | 1500 | 6R2       | 6.2       |               | 500             | 1500 | 510       | 51        | F, G, J, K, M |                 |      | 391       | 390       |      |                 |      |
| 1R2       | 1.2       |         |                 |      | 6R8       | 6.8       |               |                 |      | 560       | 56        |               |                 |      | 431       | 430       |      |                 |      |
| 1R3       | 1.3       |         |                 |      | 7R5       | 7.5       | B, C, J, K, M |                 |      | 620       | 62        |               |                 |      | 471       | 470       |      |                 |      |
| 1R4       | 1.4       |         |                 |      | 8R2       | 8.2       |               |                 |      | 680       | 68        |               |                 |      | 511       | 510       |      | 100             |      |
| 1R5       | 1.5       |         |                 |      | 9R1       | 9.1       |               |                 |      | 750       | 75        |               |                 |      | 561       | 560       |      |                 |      |
| 1R6       | 1.6       |         |                 |      | 100       | 10        |               |                 |      | 820       | 82        |               |                 |      | 621       | 620       |      |                 |      |
| 1R7       | 1.7       |         |                 |      | 110       | 11        |               |                 |      | 910       | 91        |               |                 |      | 681       | 680       |      |                 |      |
| 1R8       | 1.8       |         |                 |      | 120       | 12        |               |                 |      | 101       | 100       |               |                 |      | 751       | 750       |      |                 |      |
| 1R9       | 1.9       |         |                 |      | 130       | 13        | F, G, J, K, M |                 |      | 111       | 110       |               |                 |      | 821       | 820       |      | 50              | 300  |
| 2R0       | 2.0       |         |                 |      | 150       | 15        |               |                 |      | 121       | 120       |               | 300             | 1000 | 911       | 910       |      |                 |      |
| 2R1       | 2.1       |         |                 |      | 160       | 16        |               |                 |      | 131       | 130       |               |                 |      | 102       | 1000      |      |                 |      |
| 2R2       | 2.2       |         |                 |      | 180       | 18        |               |                 |      |           |           |               |                 |      |           |           |      |                 |      |

VRMS = 0.707 X WVDC

• SPECIAL VALUES, TOLERANCES, HIGHER WVDC AND MATCHING AVAILABLE. PLEASE CONSULT FACTORY.  
NOTE: EXTENDED WVDC DOES NOT APPLY TO CDR PRODUCTS.

## ATC PART NUMBER CODE

Series ATC100 B 91 0 J W 500 X T Packaging

Case Size \_\_\_\_\_ T - Tape and Reel, 1000 pc. qty.\*

Capacitance Code: \_\_\_\_\_ TV - Vertical Orientation of Product, Tape and Reel, 1000 pc. qty.\*

First 2 significant digits for capacitance.

R=Decimal Point I - Special Packaging. Consult Factory.

Indicates number of zeros following digits of capacitance in picofarads except for decimal values. \*Consult ATC for other quantities

Capacitance Tolerance \_\_\_\_\_ ATC Cap-Pac® packaging (100 pc. qty. std.) is also available.

For this option, leave last field blank.

Laser Marking

WVDC

Termination Code

| CAPACITANCE TOLERANCE |         |          |         |     |     |     |      |      |
|-----------------------|---------|----------|---------|-----|-----|-----|------|------|
| Code                  | B       | C        | D       | F   | G   | J   | K    | M    |
| Tol.                  | ±0.1 pF | ±0.25 pF | ±0.5 pF | ±1% | ±2% | ±5% | ±10% | ±20% |

The above part number refers to a 100 B Series (case size B) 91 pF capacitor, J tolerance (±5%), 500 WVDC, with W termination (Tin /Lead, Solder Plated over Nickel Barrier), laser marking and Tape and Reel packaging.

ATC accepts orders for our parts using designations **with** or **without** the "ATC" prefix. Both methods of defining the part number are equivalent, i.e., part numbers referenced with the "ATC" prefix are interchangeable to parts referenced without the "ATC" prefix. Customers are free to use either in specifying or procuring parts from American Technical Ceramics.

For additional information and catalogs contact your ATC representative or call direct at (+1-631) 622-4700.

Consult factory for additional performance data.











**A M E R I C A N T E C H N I C A L C E R A M I C S**

ATC North America  
sales@atceramics.com

ATC Europe  
sales@atceramics.com

ATC Asia  
sales@atceramics-asia.com

# ATC 100 B Capacitors: Mechanical Configurations

| ATC<br>SERIES<br>& CASE<br>SIZE | ATC<br>TERM.<br>CODE | MIL-PRF-<br>55681 | CASE SIZE<br>& TYPE                                                                                                                                | OUTLINES<br><br>W/T IS A<br>TERMINATION SURFACE                                                | BODY DIMENSIONS<br>INCHES (mm)                    |                            |                     | LEAD AND TERMINATION<br>DIMENSIONS AND MATERIALS |                                                                         |                                          |                                  |      |    |         |                                                                                                                                    |                                                                                                |                            |  |  |  |                           |                                          |
|---------------------------------|----------------------|-------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|---------------------------------------------------|----------------------------|---------------------|--------------------------------------------------|-------------------------------------------------------------------------|------------------------------------------|----------------------------------|------|----|---------|------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|----------------------------|--|--|--|---------------------------|------------------------------------------|
|                                 |                      |                   |                                                                                                                                                    |                                                                                                | LENGTH<br>(L)                                     | WIDTH<br>(W)               | THICKNESS<br>(T)    | OVERLAP<br>(Y)                                   | MATERIALS                                                               |                                          |                                  |      |    |         |                                                                                                                                    |                                                                                                |                            |  |  |  |                           |                                          |
| 100B                            | W                    | CDR14BG           | <div>B</div> <div></div> <div>Solder Plate.1</div>                | <div></div>   | .110<br>+.020 -.010<br>(2.79 +0.51<br>-0.25)      | .110 ±.015<br>(2.79 ±0.38) | .102 (2.59)<br>max. | .015 (0.38)<br>±.010 (0.25)                      | TIn /Lead, Solder Plated over<br>Nickel Barrier Termination             |                                          |                                  |      |    |         |                                                                                                                                    |                                                                                                |                            |  |  |  |                           |                                          |
| 100B                            | P                    | CDR14BG           | <div>B</div> <div></div> <div>Pellet</div>                        | <div></div>   | .110<br>+.035 -.010<br>(2.79<br>+0.89 -0.25)      | .110 ±.015<br>(2.79 ±0.38) |                     |                                                  | Heavy Tin/Lead Coated,<br>over<br>Nickel Barrier Termination            |                                          |                                  |      |    |         |                                                                                                                                    |                                                                                                |                            |  |  |  |                           |                                          |
| 100B                            | T                    | N/A               | <div>B</div> <div></div> <div>Solderable<br/>Nickel Barrier</div> | <div></div>   | .110<br>+.020 -.010<br>(2.79 +0.51<br>-0.25)      | .110 ±.015<br>(2.79 ±0.38) |                     |                                                  | <b>RoHS Compliant</b><br>Tin Plated over<br>Nickel Barrier Termination  |                                          |                                  |      |    |         |                                                                                                                                    |                                                                                                |                            |  |  |  |                           |                                          |
| 100B                            | CA                   | CDR13BG           | <div>B</div> <div></div> <div>Gold Chip</div>                     | <div></div>   | .110 ±0. 15<br>020 -.010<br>(2.79<br>+0.51 -0.25) | .110 ±.015<br>(2.79 ±0.38) |                     |                                                  | <b>RoHS Compliant</b><br>Gold Plated over<br>Nickel Barrier Termination |                                          |                                  |      |    |         |                                                                                                                                    |                                                                                                |                            |  |  |  |                           |                                          |
| 100B                            | MS                   | CDR21BG           | <div>B</div> <div></div> <div>Microstrip</div>                    | <div></div>   | .135 ±.015<br>(3.43 ±0.38)                        | .110 ±.015<br>(2.79 ±0.38) | .120 (3.05)<br>max. | N/A                                              | Length<br>(L <sub>L</sub> )                                             | Width<br>(W <sub>L</sub> )               | Thickness<br>(T <sub>L</sub> )   |      |    |         |                                                                                                                                    |                                                                                                |                            |  |  |  |                           |                                          |
| 100B                            | AR                   | CDR22BG           | <div>B</div> <div></div> <div>Axial Ribbon</div>                 | <div></div>  |                                                   |                            | .102 (2.59)<br>max. |                                                  | .250<br>(6.35)<br>min.                                                  | .093<br>±.005<br>(2.36<br>±0.13)         | .004<br>±.001<br>(.102<br>±.025) |      |    |         |                                                                                                                                    |                                                                                                |                            |  |  |  |                           |                                          |
| 100B                            | RR                   | CDR24BG           | <div>B</div> <div></div> <div>Radial Ribbon</div>               | <div></div> |                                                   |                            |                     |                                                  |                                                                         |                                          |                                  | 100B | RW | CDR23BG | <div>B</div> <div></div> <div>Radial Wire</div> | <div></div> | .145 ±.020<br>(3.68 ±0.51) |  |  |  | .500<br>(12.7)in.<br>min. | #26 AWG.,<br>.016 (.406) dia.<br>nominal |
| 100B                            | RW                   | CDR23BG           | <div>B</div> <div></div> <div>Radial Wire</div>                 | <div></div> | .145 ±.020<br>(3.68 ±0.51)                        |                            |                     |                                                  | .500<br>(12.7)in.<br>min.                                               | #26 AWG.,<br>.016 (.406) dia.<br>nominal |                                  |      |    |         |                                                                                                                                    |                                                                                                |                            |  |  |  |                           |                                          |
| 100B                            | AW                   | CDR25BG           | <div>B</div> <div></div> <div>Axial Wire</div>                  | <div></div> |                                                   |                            |                     |                                                  |                                                                         |                                          |                                  |      |    |         |                                                                                                                                    |                                                                                                |                            |  |  |  |                           |                                          |

Additional lead styles available: Narrow Microstrip (NM), Narrow Axial Ribbon (NA) and Vertical Narrow Microstrip (H). Other lead lengths are available; consult factory. All leads are high purity silver attached with high temperature solder and are **RoHS** compliant. For a complete military catalog, request American Technical Ceramics document ATC 001-818.








A M E R I C A N   T E C H N I C A L   C E R A M I C S

ATC North America  
sales@atceramics.com

ATC Europe  
sales@atceramics.com

ATC Asia  
sales@atceramics-asia.com

# ATC 100 B Non-Magnetic Capacitors: Mechanical Configurations

| ATC<br>SERIES<br>& CASE<br>SIZE | ATC<br>TERM.<br>CODE | MIL-PRF-<br>55681          | CASE SIZE<br>& TYPE                                                                                                        | OUTLINES<br><br>W/T IS A<br>TERMINATION SURFACE                                     | BODY DIMENSIONS<br>INCHES (mm)               |                               |                       | LEAD AND TERMINATION<br>DIMENSIONS AND MATERIALS |                                                                                 |                                  |                                |
|---------------------------------|----------------------|----------------------------|----------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------|-------------------------------|-----------------------|--------------------------------------------------|---------------------------------------------------------------------------------|----------------------------------|--------------------------------|
|                                 |                      |                            |                                                                                                                            |                                                                                     | LENGTH<br>(L)                                | WIDTH<br>(W)                  | THICKNESS<br>(T)      | OVERLAP<br>(Y)                                   | MATERIALS                                                                       |                                  |                                |
| 100B                            | WN                   | Meets<br>Require-<br>ments | B<br><br>Non-Mag<br>Solder Plate          |    | .110<br>+.025 -.010<br>(2.79 +0.64<br>-0.25) | 110 ±.015<br>(2.79 ±0.38)     | .102 (2.59)<br>max    | .015 (0.38)<br>±.010 (0.25)                      | Tin/Lead, Solder Plated<br>over<br>Non-Magnetic Barrier<br>Termination          |                                  |                                |
| 100B                            | PN                   | Meets<br>Require-<br>ments | B<br><br>Non-Mag<br>Pellet                |    | .110<br>+.035 -.010<br>(2.79 +0.89<br>-0.25) | 110 ±.015<br>(2.79 ±0.38)     |                       |                                                  | Heavy Tin/Lead Coated,<br>over<br>Non-Magnetic Barrier<br>Termination           |                                  |                                |
| 100B                            | TN                   | Meets<br>Require-<br>ments | B<br><br>Non-Mag<br>Solderable<br>Barrier |    | .110<br>+.025 -.010<br>(2.79 +0.64<br>-0.25) | 110 ±.015<br>(2.79 ±0.38)     |                       |                                                  | <b>RoHS Compliant</b><br>Tin Plated over<br>Non-Magnetic<br>Barrier Termination |                                  |                                |
| 100B                            | MN                   | Meets<br>Require-<br>ments | B<br><br>Non-Mag<br>Microstrip            |    | .135 ±.015<br>(3.43<br>±0.38)                | .110 ±.015<br>(2.79<br>±0.38) | .120 (3.05)<br>max.   | N/A                                              | Length<br>(L <sub>L</sub> )                                                     | Width<br>(W <sub>L</sub> )       | Thickness<br>(T <sub>L</sub> ) |
| 100B                            | AN                   | Meets<br>Require-<br>ments | B<br><br>Non-Mag<br>Axial Ribbon          |    |                                              |                               | .250<br>(6.35)<br>min |                                                  | .093<br>±.005<br>(2.36<br>±0.13)                                                | .004<br>±.001<br>(.102<br>±.025) |                                |
| 100B                            | FN                   | Meets<br>Require-<br>ments | B<br><br>Non-Mag<br>Radial Ribbon         |   |                                              |                               |                       |                                                  |                                                                                 |                                  |                                |
| 100B                            | RN                   | Meets<br>Require-<br>ments | B<br><br>Non-Mag<br>Radial Wire         |  | .145 ±.020<br>(3.68<br>±0.51)                |                               |                       |                                                  |                                                                                 |                                  |                                |
| 100B                            | BN                   | Meets<br>Require-<br>ments | B<br><br>Non-Mag<br>Axial Wire          |  |                                              |                               |                       |                                                  |                                                                                 |                                  |                                |

Additional lead styles available: Narrow Microstrip (DN), Narrow Axial Ribbon (GN) and Vertical Narrow Microstrip (HN). Other lead lengths are available; consult factory. All leads are high purity silver attached with high temperature solder and are **RoHS** compliant.

## Suggested Mounting Pad Dimensions

Horizontal  
Electrode Orientation

Vertical  
Electrode Orientation

Case B Vertical Mount

| Cap Value     | Pad Size     | A Min. | B Min. | C Min. | D Min. |
|---------------|--------------|--------|--------|--------|--------|
| 0.1 pF        | Normal       | .065   | .050   | .075   | .175   |
|               | High Density | .045   | .030   | .075   | .135   |
| 0.2 pF        | Normal       | .090   | .050   | .075   | .175   |
|               | High Density | .070   | .030   | .075   | .135   |
| 0.3 to 510 pF | Normal       | .110   | .050   | .075   | .175   |
|               | High Density | .090   | .030   | .075   | .135   |
| > 510 pF      | Normal       | .120   | .050   | .075   | .175   |
|               | High Density | .100   | .030   | .075   | .135   |

Horizontal Mount

|            |              |      |      |      |      |
|------------|--------------|------|------|------|------|
| All values | Normal       | .130 | .050 | .075 | .175 |
|            | High Density | .110 | .030 | .075 | .135 |

AMERICAN TECHNICAL CERAMICS


ATC North America  
sales@atceramics.com

ATC Europe  
saleseur@atceramics.com


ATC Asia  
sales@atceramics-asia.com

# ATC 100 B Performance Data


**ESR VS. CAPACITANCE  
ATC SERIES 100, CASE B**




**Q VS. CAPACITANCE  
ATC SERIES 100, CASE B**




**ESR VS. CAPACITANCE  
ATC SERIES 100, CASE B**




**Q VS. CAPACITANCE  
ATC SERIES 100, CASE B**



**SERIES RESONANCE VS. CAPACITANCE  
ATC SERIES 100, CASE B**



**CAPACITANCE CHANGE VS. TEMPERATURE  
ATC SERIES 100, CASE B**



**A M E R I C A N   T E C H N I C A L   C E R A M I C S**


ATC North America  
sales@atceramics.com

ATC Europe  
sales@atceramics.com


ATC Asia  
sales@atceramics-asia.com

# ATC 100 B Performance Data


**CURRENT RATING VS. CAPACITANCE  
ATC SERIES 100, CASE B**



**CURRENT RATING VS. CAPACITANCE  
ATC SERIES 100, CASE B**



**CURRENT RATING VS. CAPACITANCE  
ATC SERIES 100, CASE B, EXTENDED VOLTAGE**



Sales of ATC products are subject to the terms and conditions contained in American Technical Ceramics Corp. Terms and Conditions of Sale (ATC document #001-992). Copies of these terms and conditions will be provided upon request. They may also be viewed on ATC's website at [www.atceramics.com/productfinder/default.asp](http://www.atceramics.com/productfinder/default.asp). Click on the link for Terms and Conditions of Sale.

ATC has made every effort to have this information as accurate as possible. However, no responsibility is assumed by ATC for its use, nor for any infringements of rights of third parties which may result from its use. ATC reserves the right to revise the content or modify its product without prior notice.

© 1996 American Technical Ceramics Corp. All Rights Reserved

ATC # 001-807 Rev. S, 8/18



**AMERICAN**

ATC North America  
sales@atceramics.com

**TECHNICAL**

ATC Europe  
sales@atceramics.com

**CERAMICS**

ATC Asia  
sales@atceramics-asia.com



THE  
ENGINEERS'  
CHOICE®

ISO 9001 REGISTERED  
COMPANY

**THE ENGINEERS' CHOICE®**

**www.atceramics.com**